



## ANYSHOP® e2

### Stylish, Reliable and Affordable

The stylish ANYSHOP® e2 is a user-friendly POS terminal. Anyone can install or replace its optional peripherals easily. Simply by turning thumb-screws, you can install or remove peripherals with a minimal effort.

The ANYSHOP® e2 also boasts of easy filing and upgrading functions due to its groundbreaking modular design that allows for hassle free storage upgrade and adding additional side USB ports in a breeze.



- Stylish Design
- Performance / Energy-Efficient Intel® Processors
- Secondary HDD or SSD Drive
- Multiple I/O Ports
- System Expandability
- Optional Color Case
- Easy Installation and Maintenance
- Onboard UPS technology to Prevent Data Loss from Power Outages

# Features & Benefits



### 1 Easy Installation Intuitively Designed POS System

The tool-less design of ANYSHOP e2 enables easy installation. Simply turn a thumb screw by hand to install or remove peripherals.

### 2 Powerful Storage Device SSD

Low-power and low-heat SSD has longer product lifecycle, and it is the non-noise storage device that is fully optimized for the use of POS system.

### 3 15" LED LCD Touch Screen

Built to be leveraged as a cashier interface or as a customer-facing display, the ANYSHOP® e2 15" LED LCD touch display provides an ideal interface for your Point-of-Sale solution.

### 4 Eco-Friendly, Low Power Backlight Display

With its advanced LED technology, this bright, high-contrast display delivers crisp images while consuming less energy than older bulb backlight displays.



### 5 Onboard UPS : Smart Battery (Optional)

UPS [Uninterruptible Power Supply function : Internal Battery] is embedded to provide backup power when there is a blackout or a momentary power failure.

### 6 High-Performance

3rd generation Intel® Core™ i7/i5/i3 Processor and DDR3-2GB RAM (MAX. 8GB) : offers superior speed.

### 7 Intel® Active Management Technology (iAMT 8.0)

Built-in remote management technologies (Remote diagnosis and repair / Power state control).

ANYSHOP® e2 can be selectively equipped with ANYSHOP® e2 D25(Intel® D2250) or ANYSHOP® e2 Q(Intel® Core™ i7/i5/i3) series.

# Options



### Color Case

- Various Colors to Choose



### Customer Display

- VFD Type
- 20 Columns x 2 Lines



### Multi-reader

- Magnetic Stripe Reader (MSR)
- Smart Card Reader (SCR)



### 2nd LCD Display

- 9.7", 12.1" LCD
- 1024 x 768 Resolution



# Specifications



	ANYSHOP® e2 Q SERIES	ANYSHOP® e2 D25
<b>CPU</b>	uPGA988 for 2nd and 3rd Generation Intel® Core™ i7/i5/i3, Intel® Pentium, Intel® Celeron Processors	Intel Atom Processor D2550 (1MB Cache, 1.86 GHz, Dual Core for Cedarview-D)
<b>Chipset</b>	Intel QM77 Intel HM76	Intel NM10
<b>Storage</b>	SATA 3 (6Gb/s) 2.5 inch HDD or SSD (Max. 2 Optional), Support AHCI (SSD : 64GB or 32GB / HDD : 320GB)	SATA 2 (3Gb/s) 2.5 inch HDD or SSD (Max. 2 Optional), Support AHCI (SSD : 64GB or 32GB / HDD: 320GB)
<b>Memory</b>	DDR3-1600MHz SODIMM Default 2GB (MAX. 8GB)	DDR3-1066MHz SODIMM 2GB (MAX. 4GB)
<b>Graphic</b>	Integrated Intel GFX	Integrated Intel GMA HD 3650
<b>AMT</b>	Support iAMT 8.0	-
<b>Display</b>		
Resolution	15" LED Backlight TFT-LCD 250 cd/m <sup>2</sup> (1024 x 768 Resolution)	
Touch screen	5-wired Resistive Touch	
<b>Internal I/O</b>		
USB	3 Ports (reserved for touch controller, SCR EMV card, MSR controller)	
Serial port	COM 5 (reserved for cash drawer port) & COM 6 (reserved for MSR)	
Display port	LVDS or VGA & COM 4 (reserved for CDP)	VGA & COM 4 (reserved for CDP)
Extension slot	Mini PCIe	
Primary display	24bit LVDS	
<b>External I/O</b>		
USB	Rear 6 (USB 3.0 x 4 ports, USB 2.0 x 2 ports) Rear 4 (USB 3.0 x 2 ports, USB 2.0 x 2 ports)	Rear 4 (USB 2.0 x 4 ports)
PS/2	1 Port (reserved for Keyboard & Mouse)	
Serial port	COM 1 ~ 3 with 5V/12V power output on 9pin	
LAN	Gigabit Ethernet x 2 ports 1 x Intel Gigabit LAN with iAMT 8.0 (Intel 82579LM) 1 x Intel Gigabit LAN with (Intel 82583V)	Realtek RTL 8111E Ethernet Controller
Audio	Realtek ALC 892 / Line-out, Mic-in	
Display port	VGA x 1 port	
<b>Options</b>		
MSR	Comply with ISO 7811, Support 1 & 2 & 3 track	
Speaker	2 x 0.8W (Stereo)	
Side USB	4 ports (USB 2.0 x 4 ports)	
SCR	EMV level 1	
Dallas	Dallas I-button reader	
Back up battery	Smart battery (supports up to 1 packs)	
Customer display	VFD type (20 x 2)	
2nd LCD	9.7", 12.1" LCD (1024 x 768 Resolution)	
2nd Storage	2nd 2.5 inch HDD / SSD storage	
Cash drawer port	1 Port	
Parallel port	1 Port	
WiFi	Mini PCIe for wireless LAN	
<b>Operating Temperature</b>	0°C ~ 40°C at 10% ~ 80% humidity	
<b>Storage Temperature</b>	-20°C ~ 60°C at 10% ~ 80% humidity	
<b>Qualification</b>	CE, FCC, KC	
<b>Power</b>	Adaptor 24V, 6A	Adaptor 12V, 5A
<b>OS Support</b>	Windows 7, Windows 8, POS Ready 7	Windows XP/Vista, Windows 7, POS Ready 2009/7
<b>Dimension (WxHxD)</b>	365 x 305 x 385(mm), 14.3 x 12 x 15.1(inch)	

\*Specifications may change without prior notice.